User Manual

Battery core Samsung battery
Input/output voltage 5V
Input current 1000Mah±5%
Output current Two USB Ports outputting simultaneously, its output current is 1000mAh.
One USB Ports outputting, its output current is 2000mAh.
Capacity 5200mAh
Charging time 5.5-6 hours (with 5V1A power adaptor)
Cycling life of battery ≥500 times
Working temperature -10℃-40℃
Store /transport temperature -20℃-50℃

Specifications:
Operating instruction when charging other devices:
1 Please use USB output port to connect the device well
2. Enter on/off button, it will begin charging within 5 seconds.
3. The power indicator lights when charging other devices.

Power indicating:
1. Enter on/off button, the capacity LED shows power quantity and will be go off after 5 seconds.
2. If the power indicator flashing, it is short of power.
3. Enter on/off button, no lighting shows that it is power off or broken.

Please read this instruction carefully before use it.
Function features:
◆ With Samsung battery core, capacity is 5200mAH.
◆ Built-in over-current protection, overcharging protection, under-voltage protection,under-loading protection, overloading protection, short circuit protection.
◆ 5 power indicator lights which can indicate relevant power clearly.
◆ Single button shuttle flying: only one button can finish all operations.
◆ Auto sleep: it can be auto sleep under non-working status to avoid power wastage.
◆ Supporting iPhone ,iPad, iPod,Blackberry,HTC,MP3,MP4, PSP, etc.

Charging status (for power bank):
Remarks:
★ Charging it every at least 4 months when non-using it for long time.
★ Please put it under dry, constant temperature and keep it away from humid and corrosive environment.
★ Don't take it down and throw it in fire.
★ If battery expanding, leaking or with foreign matter, please stop using it.

Capacity LED Status Capacity Percentage
Four LEDs all on 100%
Only three LEDs on ≥75%
Only two LEDs on ≥50%
Only one LED on ≥25%

Product pictures: